

KENWOOD

NEXEDGE®

NX-3220/3320

NEXEDGE® VHF/UHF MULTI-PROTOCOL DIGITAL & ANALOG PORTABLE RADIOS

NXDN® **DMR** **Gen2** **Bluetooth®** **GPS** **FleetSync®**

This versatile handheld radio supports both NXDN® and DMR digital protocols as well as mixed digital & FM analog operation, enabling it to serve with distinction in a wide range of enterprise and operation critical applications. Compact yet designed with durability in mind, it's packed with convenient features like Bluetooth® for hands-free operation and built-in GPS. Three different models are available: Full Keypad model with LCD, Standard Keypad model with LCD and a large 4-way D-pad, and the Basic Model without LCD or keypad. Additionally, for expansion capability a software license certification system facilitates extensive customization.

● FEATURE HIGHLIGHTS

- **Multi-protocol digital** radio: Designed to operate NXDN® or DMR digital, and FM analog protocols
- **NXDN®** Conventional and Type-C & Gen2 Trunking
- **DMR** Tier II & Site Roaming
- **Mixed Digital & FM Analog Operation** allows gradual migration at your own pace
- **4-Line** Basic Frame (2-Line Main/Sub-LCD, icon & key guide) / 14 Characters
- **5-Line** Text Message Frame (3 Lines of Text, icon & key guide)
- **7-color** Light Bar Indicator on the top panel
- **4-way** Directional-pad (**D-pad**) for intuitive control and operation
- **Built-In GPS Receiver/Antenna** for effective fleet management
- **Built-in Bluetooth®** for hands-free operation - Applicable Bluetooth profiles: HSP (Headset Profile provided) and SPP (Serial Port Profile available as an option)
- Renowned **KENWOOD Audio Quality** can be achieved with **Active Noise Reduction (ANR)** that utilizes built-in DSP
- Software DES and AES Encryptions for NXDN Conventional/Trunking and DMR Conventional protocols
- **Built-in Motion Sensor** (Man-down, Stationary and Motion Detection)
- **IP54/55/67** and **MIL-STD-810 C/D/E/F/G**

● GENERAL FEATURES

- 1 Watt Audio Output Power
- UHF: 120 MHz capability
- Available models: Full Keypad (w/ LCD and full keypad), Standard Keypad (w/ LCD and 4-way large D-pad/4 key), and Basic (w/o LCD and keypad)
- 260 CH/128 Zones (64 CH/4 Zones for Basic model)
- Maximum of 1,000 CH/Radio with option
- Paging Call
- Emergency Call
- Status/Text Message
- Remote Stun/Kill/Check

● DIGITAL – NXDN® MODE

- NXDN Type-C & Gen2 Trunked
- NXDN Conventional
- 6.25 & 12.5 kHz Channels
- All Group Call
- Over-the-Air Alias (OAA)
- Over-the-Air Programming (OTAP)

● DIGITAL – DMR MODE

- Complies with ETSI DMR Tier II standards
- Two-slot TDMA in 12.5 kHz channels
- Call Interruption
- Dual-slot Direct Mode
- ARC4 Encryption
- Energy Efficient

● ANALOG - FM MODE

- Conventional & LTR Trunking
- FleetSync/II: PTT ID ANI / Caller ID Display, Selective Group Call, Emergency Status / Text Messages
- MDC-1200: PTT ID ANI / Caller ID Display, Emergency, Radio Check / Inhibit
- QT / DQT, 2-Tone
- Built-in Voice Inversion Scrambler



Full Keypad Model

Standard & Basic Models
(Not proportionately accurate)

Options

<p>■ KNB-55L/57L Li-ion Battery Pack (7.4 V/1480 mAh, 7.4 V/2000 mAh)</p>	<p>■ KMB-30 Mounting Bracket (for KSC-256)</p>	<p>■ KRA-26 VHF Helical Antenna</p>	<p>■ KHS-7A Lightweight Single Muff Headset</p>	<p>■ KHS-27A Head Set (with D-Ring In-Line PTT)</p>
<p>■ KNB-56N Ni-MH Battery Pack (7.2 V/1400 mAh)</p>	<p>■ KVC-4 Vehicular Charger</p>	<p>■ KRA-27 UHF Whip Antenna</p>	<p>■ KHS-8 2-wire Palm Mic with Earphone (Black)</p>	<p>■ KBH-11 Belt Clip (2.5")</p>
<p>■ KBP-5 Battery Case (6 AA)</p>	<p>■ KRA-22 VHF Low Profile Helical Antenna</p>	<p>■ KRA-28 Broadband VHF Whip Antenna</p>	<p>■ KHS-10-BH Headset (Single Muff Single Muff & In-line PTT Heavy Duty Behind-the-Head)</p>	<p>■ KPG-180P OTAP Manager</p>
<p>■ KSC-25LSK/25SK Rapid Charger (Li-ion Only/Tri-Chem)</p>	<p>■ KRA-23 UHF Low Profile Helical Antenna</p>	<p>■ KEP-2 Earphone Kit for KMC-45D (2.5mm plug)</p>	<p>■ KHS-22 Head Set</p>	<p>■ KLH-208 Leather Case</p>
<p>■ KSC-256K Multiple Charger (6-pocket)</p>	<p>■ KRA-25 High Gain Whip Antenna</p>	<p>■ KMC-45D Speaker Microphone (IP54/55 & TDMA)</p>	<p>■ KHS-26 Head Set (with Ear Bud In-Line PTT)</p>	

All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Main Specifications

	NX-3220	NX-3320		NX-3220	NX-3320
GENERAL			RECEIVER		
Frequency Range	136-174 MHz	400-520 MHz	Sensitivity		
Max. Channels Per Radio	Up to 1000 CH with option		NXDN® 6.25 kHz Digital (3% BER)	0.20 µV	
Number of Channels	260 (64 for no LCD models)		NXDN® 12.5 kHz Digital (3% BER)	0.25 µV	
Number of Zones	128 (4 for no LCD models)		DMR 12.5 KHz Digital (5% BER)	0.30 µV	
Channel Spacing			DMR 12.5 KHz Digital (1% BER)	0.45 µV	
Analog	12.5/15/25*/30* kHz	12.5/25* kHz	Analog (12dB SINAD)	0.25 µV	
Digital	6.25kHz/12.5 kHz	6.25kHz/12.5kHz	Selectivity		
Power Supply	7.5V DC ± 20%		Analog @ 12.5 kHz	65 dB	
Battery Life	(FDMA/TDMA) 5-5-90		Analog @ 25 kHz	72 dB	
KNB-55L (1,480 mAh)	Approx. 8 hours	Approx. 9.5 hours	Intermodulation	70 dB	
KNB-56N (1,400 mAh)	Approx. 8 hours	Approx. 9 hours	Spurious Rejection	70 dB	
KNB-57L (2,000 mAh)	Approx. 11 hours	Approx. 13.5 hours	Audio Distortion	3%	
Operating Temperature	-22°F to +140°F (-30°C to +60°C)		Audio Output Power	500 mW/8Ω (3% Distortion) / 1,000 mW/8Ω (5% Distortion)	
Frequency Stability	±2.0 ppm		TRANSMITTER		
Dimensions	(W x H x D) Projections Not Included		RF Power Output (High / Mid / Low)	5 W / 4 W / 1 W	
Radio Full Keypad Model	2.20 x 4.71 x 1.43 in (56 x 119.6 x 36.4 mm)		Spurious Emission	-70 dB	
KNB-55L (1,480 mAh)	2.20 x 4.71 x 1.43 in (56 x 119.6 x 36.4 mm)		FM Hum & Noise		
KNB-56N (1,400 mAh)	2.20 x 4.71 x 1.68 in (56 x 119.6 x 42.7 mm)		Analog @ 12.5 kHz	40 dB	
KNB-57L (2,000 mAh)	2.20 x 4.71 x 1.53 in (56 x 119.6 x 39 mm)		Analog @ 25kHz	45 dB	
Weight Radio Full Keypad Model	7.8 oz (220 g)		Audio Distortion	3%	
KNB-55L (1,480 mAh)	11.1 oz (315 g)		Digital Protocol	ETSI TS 102 361-1, -2, -3	
KNB-56N (1,400 mAh)	14.5 oz (410 g)		Emission Designator	16K0F3E*, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 7K60FXD, 7K60FXE, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	
KNB-57L (2,000 mAh)	12.0 oz (340 g)				
FCC ID	K44479000	K44479100			
IC Certification	282F-479000	282F-479100			

*1 25 and 30 kHz are not included in the models sold in the USA or US territories. Analog measurements made per TIA603. Specifications are measured according to applicable standards. Specifications shown are typical and subject to change without notice, due to advancements in technology.

The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. NXDN® is a trademark of JVCKENWOOD Corporation and Icom Inc. NEXEDGE® is a registered trademark of JVCKENWOOD Corporation. FleetSync® is a registered trademark of JVCKENWOOD Corporation. All other trademarks are the property of their respective holders.

Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
International Protection Standard					
Dust & Water Protection*	IP54/55/67				

*Radio must equip 2PIN accessory cover.



JVCKENWOOD USA Corporation
 Communications Sector Headquarters
 3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265
 Order Administration/Distribution
 P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745
www.kenwood.com/usa

JVCKENWOOD Canada Inc.
 Canadian Headquarters and Distribution
 6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8
www.kenwood.com/ca



ISO9001 Registered
 JVCKENWOOD Corporation